



FULL-NITRILE 14-650







CHARACTERISTICS

- \cdot Glove with double nitrile coating ("Sandy Finish")
- · Polyester liner (15 gauge) with tricot cuff
- · The seamless liner affords optimal comfort
- The Sandy Finish coating with its unique open structure provides optimal grip, especially in oily work environments
- The glove's impermeability to water and oil makes it ideally suited for activities in wet or oily work environments
- · Prevents allergic reactions when coming into contact with oils
- · Excellent comfort due to the extremely good fit
- Their dark colour makes these gloves excellently suitable for use in environments with a certain level of contamination

Article number: 1.14.650.00

SUITABLE FOR ACTIVITIES IN E.G.

- \cdot Building and construction
- · Wet working conditions
- · Maintenance of public works
- · Transport & logistics
- · Civil and hydraulic engineering
- · Agriculture

COLOUR

Black/blue

SIZES

8/M to 11/XXL incl.

PACKAGING

- \cdot 1 pair per polybag
- · 12 pairs per bundle
- · 144 pairs per outer box

EN388:2016+A1:2018



C E N ISO 21420:2020



PRODUCT INFORMATION

SIZE	ARTICLE NO.	EAN CODE 1 PAIR (POLYBAG)	EAN CODE 12 PAIRS (BUNDLE)	EAN CODE 144 PAIRS (OUTER BOX)
8/M	1.14.650.08	8718249041471	8718249041488	8718249041495
9/L	1.14.650.09	8718249041501	8718249041518	8718249041525
10/XL	1.14.650.10	8718249041532	8718249041549	8718249041556
11/XXL	1.14.650.11	8718249041563	8718249041570	8718249041587

COLOUR BINDING/OVERLOCKING

Sizes	8/M	9/L	10/XL	11/XXL
Colour binding/overlocking	green	blue	grey	black

CLARIFICATION OF PICTOGRAMS

EN388:2016+A1:2018







Protection against mechanical hazards

- A = Scuff resistance (0-4)
- B = Cut resistance (0-5)
- C = Tear resistance (0-4)
- D = Puncture resistance (0-4)
- E = Cut resistance (in accordance with EN ISO 13977 (A to F)
- F = Impact resistance (optional) (P = Passed)

Note: X = untested or not applicable

STORAGE CONDITIONS

The gloves should be kept in a clean, cool and dry place and not kept compressed in their original packaging. Do not expose the gloves to direct sunlight. Make sure that the packaging and the gloves are not damaged during shipping.

TESTING INSTITUTE

These gloves are certified by: CTC (Notified Body no. 0075), 4 Rue Hermann Frenkel 69367 Lyon, Cedex 07, France.

DECLARATION OF CONFORMITY

For a copy of the declaration of conformity, we refer you to the following link: www.oxxa.work/doc

RELATED PRODUCTS



X-PRO-DRY 51-300 Art. no. 1.51.300.00



X-PRO-WINTER-DRY 51-870

Art. no. 1.51.870.00

YOUR SUPPLIER: