

OXXA[®]
PREMIUM



FIT



CUT
RESISTANCE



GRIP

X-DIAMOND- PRO

51-775 CUT C



TOUCHSCREEN
CAPABILITY



CHARACTERISTICS

- Polyurethane coating on the palm and fingers
- Polyester/spandex/Dyneema[®] Diamond liner (15 gauge)
- Seamless glove
- Elastic knitted wrist cuff
- The thin and light PU coating offers a high level of comfort, fingertip sensitivity and flexibility
- The 15-gauge knitted liner features Dyneema[®] Diamond Technology fibres, which offer very high cut resistance and excellent comfort
- Dyneema[®] Diamond is the strongest fibre in the world, allowing us to make very strong and cut-resistant safety gloves that are also very comfortable to wear
- The extra long cuff provides maximum hand and wrist protection
- Sanitised[®] treatment to inhibit bacterial growth, minimise odours and encourage freshness
- The conductive coating on the palm and fingers allows the user to effortlessly operate touchscreen devices

Article number: 1.51.775.00

SUITABLE FOR ACTIVITIES IN E.G.

- Glass industry
- Metal industry
- Construction
- Automotive
- Government services
- Assembly
- Paper industry
- Machine maintenance

COLOUR

Grey/black

SIZES

7/S to 11/XXL incl.

PACKAGING

- 1 pair per polybag
- 12 pairs per bundle
- 144 pairs per outer box

EN388:2016



4X43C



EN 420:2003+A1:2009

PRODUCT INFORMATION

SIZE	ARTICLE NO.	EAN CODE 1 PAIR (POLYBAG)	EAN CODE 12 PAIRS (BUNDLE)	EAN CODE 144 PAIRS (OUTER BOX)
7/S	1.51.775.07	8718249062315	8718249062322	8718249062339
8/M	1.51.775.08	8718249062346	8718249062353	8718249062360
9/L	1.51.775.09	8718249062377	8718249062384	8718249062391
10/XL	1.51.775.10	8718249062407	8718249062414	8718249062421
11/XXL	1.51.775.11	8718249062438	8718249062445	8718249062452

COLOUR BINDING/OVERLOCKING

Sizes	7/S	8/M	9/L	10/XL	11/XXL
Colour binding/overlocking	yellow	green	blue	grey	black

CLARIFICATION OF PICTOGRAMS

EN388:2016



4X43C

EN388:2016



abcdef

Protection against mechanical hazards

A = Scuff resistance (0-4)

B = Cut resistance (0-5)

C = Tear resistance (0-4)

D = Puncture resistance (0-4)

E = Cut resistance (in accordance with EN ISO 13977 (A to F))

F = Impact resistance (optional) (P = Passed)

Note: X = untested or not applicable

STORAGE CONDITIONS

The gloves should be kept in a clean, cool and dry place and not kept compressed in their original packaging. Do not expose the gloves to direct sunlight. Make sure that the packaging and the gloves are not damaged during shipping.

TESTING INSTITUTE

These gloves are certified by: CTC (Notified Body no. 0075), 4 Rue Hermann Frenkel 69367 Lyon, Cedex 07, France.

DECLARATION OF CONFORMITY

For a copy of the declaration of conformity, we refer you to the following link: www.oxxa-safety.com/doc

YOUR SUPPLIER:

RELATED PRODUCTS



X-DIAMOND-PRO

51-770 CUT B

Art. no. 1.51.770.00



X-DIAMOND-PRO

51-785 CUT D

Art. no. 1.51.785.00