



FIT





COLD



GRIP

# X-GRIP THERMO

## 51-850



### CHARACTERISTICS

- Latex foam coating on the palm and fingers
- Acrylic terry liner (10 gauge)
- Seamless glove
- Elastic knitted wrist cuff
- Fully coated thumb for extra safety
- The brushed inner lining is soft and comfortable and keeps your hands warm in extremely low temperatures
- Optimum comfort during prolonged use
- Excellent grip, even when working in wet, oily and greasy conditions
- Excellent ventilation on the back of the hand, ensuring a good absorption of perspiration
- The orange fluorescent colour of the liner provides excellent visibility

**Article number: 1.51.850.00**

### SUITABLE FOR ACTIVITIES IN E.G.

- Construction
- Scaffolding
- Government services
- Transport & logistics
- Recycling
- Civil and hydraulic engineering
- Agriculture
- Shipping

### COLOUR

Grey/fluorescent orange

### SIZES

8/M to 11/XXL incl.

### PACKAGING

- 1 pair per polybag
- 12 pairs per bundle
- 72 pairs per outer box

EN388:2016



2242X

EN511:2006



X2X



EN 420:2003+A1:2009



### PRODUCT INFORMATION

SIZE	ARTICLE NO.	EAN CODE 1 PAIR (POLYBAG)	EAN CODE 12 PAIRS (BUNDLE)	EAN CODE 72 PAIRS (OUTER BOX)
8/M	1.51.850.08	8718249037825	8718249037832	8718249037849
9/L	1.51.850.09	8718249027468	8718249027475	8718249027482
10/XL	1.51.850.10	8718249027499	8718249027505	8718249027512
11/XXL	1.51.850.11	8718249027529	8718249027536	8718249027543

### COLOUR BINDING/OVERLOCKING

Sizes	8/M	9/L	10/XL	11/XXL
Colour binding/overlocking	green	blue	grey	black

### CLARIFICATION OF PICTOGRAMS

EN388:2016



2242X

EN388:2016



abcdef

#### Protection against mechanical hazards

A = Scuff resistance (0-4)  
 B = Cut resistance (0-5)  
 C = Tear resistance (0-4)  
 D = Puncture resistance (0-4)  
 E = Cut resistance (in accordance with EN ISO 13977 (A to F))  
 F = Impact resistance (optional) (P = Passed)

EN511:2006



X2X

EN511:2006



abcdef

#### Protection against cold

A = Radiative cooling (0-4)  
 B = Contact cold (0-4)  
 C = Watertightness (0-1)

Note: X = untested or not applicable

### STORAGE CONDITIONS

The gloves should be kept in a clean, cool and dry place and not kept compressed in their original packaging. Do not expose the gloves to direct sunlight. Make sure that the packaging and the gloves are not damaged during shipping.

### TESTING INSTITUTE

These gloves are certified by: CTC (Notified Body no. 0075),  
 4 Rue Hermann Frenkel 69367 Lyon, Cedex 07, France

### DECLARATION OF CONFORMITY

For a copy of the declaration of conformity, we refer you to the following link: [www.oxxa-safety.com/doc](http://www.oxxa-safety.com/doc)

### YOUR SUPPLIER:

### RELATED PRODUCTS



**OXXA X-FROST 51-860**

Art. no. 1.51.860.00



**OXXA X-GRIP 51-000**

Art. no. 1.51.000.00