

# Jersette 300

## DESCRIPTION AND GENERAL PROPERTIES

**Material** Natural latex  
**Length (inches)** 11.42-12.99  
**Thickness (inches)** 0.045  
**Wrist** Scalloped cuff  
**Colour/Color** Blue  
**Interior finish** Textile support  
**Exterior finish** Smooth  
**Size / EAN** 5 6 7 8 9 10  
**Packaging** 1 pair/bag - 5 pairs/box - 50 pairs/carton  
**Complementary information** Guaranteed without silicone



## PERFORMANCE RESULTS

Certification category 2



X1XXXX

Type B



KPT



2131X

### Legends

#### EN 388 MECHANICAL HAZARDS



##### PERFORMANCE LEVELS

0-4 0-5 0-4 0-4 A-F (P)  
 Impact protection  
 Cut resistance according to ISO 13997  
 Puncture resistance  
 Tear resistance  
 Blade cut resistance  
 Abrasion resistance

#### EN 407 THERMAL RISKS heat and fire



##### PERFORMANCE LEVELS

0-4 0-4 0-4 0-4 0-4 0-4  
 Resistance to large quantities of molten metal  
 Resistance to small drops of molten metal  
 Radiant heat resistant  
 Convective heat resistance  
 Contact heat resistance  
 Burning behaviour

#### CHEMICAL RISKS

##### EN ISO 374-1



Type A

U V W X Y Z

A Methanol  
 B Acetone  
 C Acetonitrile  
 D Dichloromethane  
 E Carbon Disulfide  
 F Toluene  
 G Diethylamine  
 H Tetrahydrofurane  
 I Ethyl acetate

##### EN ISO 374-1



Type B

X Y Z

J n-Heptane  
 K Sodium hydroxide 40%  
 L Sulphuric acid 96%  
 M Nitric acid 65%  
 N Acetic acid 99%  
 O Ammonia 25%  
 P Hydrogen peroxide 30%  
 S Hydrofluoric acid 40%  
 T Formaldehyde 37%

##### EN ISO 374-1



Type C

#### MICRO-ORGANISMS

##### EN ISO 374-5



Protection against bacteria, fungi

##### EN ISO 374-5



Protection against bacteria, fungi, virus

##### VIRUS



#### COLD HAZARDS

##### PERFORMANCE LEVELS

0-4 0-4 0 or 1  
 Water permeability  
 Contact cold resistance  
 Convective cold resistance



EN 511

#### RADIOACTIVE CONTAMINATION



CUT

#### CUT RESISTANCE

A1 ≥ 200 G A4 ≥ 1500 G A7 ≥ 4000 G  
 A2 ≥ 500 G A5 ≥ 2200 G A8 ≥ 5000 G  
 A3 ≥ 1000 G A6 ≥ 3000 G A9 ≥ 6000 G

For more details: [www.mapa-pro.com](http://www.mapa-pro.com)

**MAPA**  
PROFESSIONAL

[www.mapa-pro.com](http://www.mapa-pro.com)

## SPECIFIC ADVANTAGES

Freedom of movement, due to the anatomical shape and excellent comfort from the seamless textile support  
Good tear-resistance  
Good resistance to many diluted acids and bases

## MAIN FIELDS OF USE

### Construction Industry (Masons / Plasterers)

Preparing and pouring mortar and cement

### Local Authorities (Cleaning)

Handling household detergents

### Aeronautics industry

Work with composite materials (resins)

## INSTRUCTIONS FOR USE

### Instructions for use

It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at the workplace may differ from the "CE"-type tests.

It is not recommended for persons sensitized to natural latex, dithiocarbamates and thiazoles to use these gloves.

Put the gloves on dry, clean hands.

Do not use the gloves in contact with a chemical for a duration in excess of the measured breakthrough time. Refer to the website [www.mapa-pro.com](http://www.mapa-pro.com) or contact the Technical Customer Service - MAPA PROFESSIONNEL ([stc.mapaspontex@mapaspontex.fr](mailto:stc.mapaspontex@mapaspontex.fr)) in order to know this breakthrough time. Use 2 pairs alternatively when in long duration contact with a solvent.

Turn the cuff end down in order to prevent a hazardous chemical from dripping onto the arm.

Inspect the gloves for cracks or snags before reusing them.

### Storage conditions

Store the gloves in their original packaging protected from direct sunlight, far from heat sources or electric equipment.

### Laundering conditions

Before taking off the gloves, clean them as appropriate :

in use with a solvent (alcohol, etc...) : rub over with a dry cloth

in use with detergents, acids or alkalies : thoroughly rinse the gloves under running water, and rub over with a dry cloth

Caution : inappropriate usage of the gloves or submitting them to a cleaning or laundering process which is not specifically recommended, can alter their performance levels.

### Drying conditions

Ensure the inside of the gloves is dry before putting them on again.

## LEGISLATION

This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council. This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).

**UE type certificate or CE type examination certificate :** 0072/014/162/09/94/0012

**Issued by the notified body nr :** 0072 - I.F.T.H. – Av. Guy de Collongue F-69134 ECULLY CEDEX