

Kronit-Proof 395

DESCRIPTION AND GENERAL PROPERTIES

- **Material** Nitrile
- **Length (cm)** 32
- **Thickness (mm)** NS
- **Wrist** Straight cuff
- **Colour/Color** Green
- **Interior finish** Textile support Mapa Technology
- **Size / EAN** 8 9 10
- **Packaging** 1 pair/bag - 12 pairs/carton
- **Complementary information** Guaranteed without silicone



PERFORMANCE RESULTS

Certification category 3

CE 0334



X2XXXX



JKL



4543

ISO 13997 defines the weight on the blade required to cut in a single movement.

Data was obtained according to ISO 13997, from the average of several measurements. As Individual specimens will obviously have greater or lesser cut resistance than the average, so this result can provide only a general indication of the cut resistance of any protective material.

Legends



**MECHANICAL
HAZARDS
EN 388**

PERFORMANCE LEVELS

0-4 0-5 0-4 0-4
 └─ Blade cut resistance
 └─ Abrasion resistance
 └─ Puncture resistance
 └─ Tear resistance



**HEAT
AND FIRE
EN 407**

PERFORMANCE LEVELS

0-4 0-4 0-4 0-4 0-4 0-4
 └─ Burning behaviour
 └─ Contact heat resistance
 └─ Convective heat resistance
 └─ Radiant heat resistant
 └─ Resistance to small drops of molten metal
 └─ Resistance to large quantities of molten metal



**LOW CHEMICAL
PROTECTION
EN 374**



**MICRO-ORGANISMS
EN 374**



**SPECIFIC CHEMICAL
PROTECTION
EN 374**

Letter Code	Chemical product
A	Methanol
B	Acetone
C	Acetonitrile
D	Dichloromethane
E	Carbon Disulfide
F	Toluene
G	Diethylamine
H	Tetrahydrofurane
I	Ethyl acetate
J	n-Heptane
K	Sodium hydroxide 40%
L	Sulphuric acid 96%



**RADIOACTIVE
CONTAMINATION
EN 421**



**COLD HAZARDS
EN 511**

PERFORMANCE LEVELS

0-4 0-4 0 or 1
 └─ Convective cold resistance
 └─ Contact cold resistance
 └─ Water permeability

For more details: www.mapa-pro.com

Kronit-Proof 395

DESCRIPTION AND GENERAL PROPERTIES

- Total hand protection, level 5 against cuts
- Entirely liquid-proof, withstanding mechanical aggression
- Proven long-lasting performance, measured after 5 washes
- Good grip for picking up wet and slippery objects safely

MAIN FIELDS OF USE

Automotive/mechanical industry

- Sheet metal
- Metal rolling, stamping and assembly
- Cutting aluminium strips

Other industries

- Collection and sorting of industrial and household waste

INSTRUCTIONS FOR USE

Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, as the conditions of use at workplace may differ from the «CE»-type tests.
- It is not recommended for persons sensitized to dithiocarbamates and thiazoles to use these gloves.
- Do not use these gloves next to moving machinery.
- Put the gloves on dry, clean hands.
- Inspect the gloves for snags or tears before reusing them.

Storage conditions

Store the gloves in their original packaging protected from light and humidity.

Laundering conditions

Clean gloves exposed to oil or grease with a dry cloth before taking them off. Caution : using the gloves or submitting them to a cleaning or laundering process which is not specifically recommended can alter their performance levels.

Drying conditions

Ensure the inside of the gloves is dry before putting them on again.

LEGISLATION

This product is not classified as hazardous according to the directive 1999/45/EC of the European Parliament and of the Council.

This product does not contain any substances of very high concern according to the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).

- CE-Type Examination Certificate

0075/014/162/09/07/0339

- Issued by the notified body nr

0075

C.T.C. – Rue H FRENKEL - F-69367 LYON CEDEX 07

- Quality assurance certificat

0334 Asqual 14 rue des Reculettes -F-75013 PARIS