

Titan 397

DESCRIPTION AND GENERAL PROPERTIES

Material Nitrile

Length (inches) 9.44-12.20 (depending on size)

Wrist Knitted wrist

Colour/Color Yellow

Interior finish Textile support

Exterior finish Smooth

Size / EAN 6 7 8 9 10

Packaging 1 pairs/bag - 10 pairs/bag - 100 pairs/carton

Complementary information Guaranteed without silicone

Available in single pack and in polybag of 10 pairs

Guaranteed without DMF



PERFORMANCE RESULTS

Certification category 2



4111X

Legends

EN 388 MECHANICAL HAZARDS



PERFORMANCE LEVELS

0-4 0-5 0-4 0-4 A-F (P)
 └─ Impact protection
 └─ Cut resistance according to ISO 13997
 └─ Puncture resistance
 └─ Tear resistance
 └─ Blade cut resistance
 └─ Abrasion resistance

EN 407 THERMAL RISKS heat and fire



PERFORMANCE LEVELS

0-4 0-4 0-4 0-4 0-4 0-4
 └─ Resistance to large quantities of molten metal
 └─ Resistance to small drops of molten metal
 └─ Radiant heat resistant
 └─ Convective heat resistance
 └─ Contact heat resistance
 └─ Burning behaviour

CHEMICAL RISKS

EN ISO 374-1



U V W X Y Z

A Methanol
B Acetone
C Acetonitrile
D Dichloromethane
E Carbon Disulfide
F Toluene
G Diethylamine
H Tetrahydrofuran
I Ethyl acetate

EN ISO 374-1



X Y Z

J n-Heptane
K Sodium hydroxide 40%
L Sulphuric acid 96%
M Nitric acid 65%
N Acetic acid 99%
O Ammonia 25%
P Hydrogen peroxide 30%
S Hydrofluoric acid 40%
T Formaldehyde 37%

EN ISO 374-1



X Y Z

MICRO-ORGANISMS

EN ISO 374-5



Protection against bacteria, fungi

EN ISO 374-5



Protection against bacteria, fungi, virus

VIRUS



COLD HAZARDS

PERFORMANCE LEVELS

0-4 0-4 0 or 1
 └─ Water permeability
 └─ Contact cold resistance
 └─ Convective cold resistance



RADIOACTIVE CONTAMINATION



CUT RESISTANCE

A1 ≥ 200 G **A4** ≥ 1500 G **A7** ≥ 4000 G
A2 ≥ 500 G **A5** ≥ 2200 G **A8** ≥ 5000 G
A3 ≥ 1000 G **A6** ≥ 3000 G **A9** ≥ 6000 G

For more details: www.mapa-pro.com

MAPA
PROFESSIONAL

www.mapa-pro.com

SPECIFIC ADVANTAGES

Excellent comfort, due to the thickness of the cotton lining and the ventilated back
Freedom of movement: dexterity and flexibility, due to the close fit to the hand
Excellent service life: good abrasion resistance
Previous name: Titanlite 397

MAIN FIELDS OF USE

Automotive/mechanical industry

Sanding
Precision mechanical work
Part assembly
Handling oily mechanical parts

Other industries

Manufacturing small electrical components
Construction materials handling

INSTRUCTIONS FOR USE

Instructions for use

It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at workplace may differ from the « CE »-type-tests.

It is not recommended for persons sensitized to dithiocarbamates and thiazoles to use these gloves.

Put the gloves on dry, clean hands.

Rub over the gloves stained with oil or grease before taking them off.

Inspect the gloves for snags or tears before reusing them.

Storage conditions

Store the gloves in their original packaging protected from light and humidity.

Laundering conditions

Caution : using the gloves or submitting them to cleaning or laundering process which is not specifically recommended can alter their performance levels.

Drying conditions

Ensure the inside of the gloves is dry before putting them on again.

LEGISLATION

This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council. This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).

UE type certificate or CE type examination certificate : 0075/014/162/07/18/1377

Issued by the notified body nr : 0075 - C.T.C - 4 rue Herman FRENKEL - F - 69367 LYON CEDEX 07