

Ultranitril 492

DESCRIPTION AND GENERAL PROPERTIES

- **Material** Nitrile
- **Length (inches)** 12.59
- **Thickness (inches)** 0.017
- **Wrist** Straight cuff
- **Colour/Color** Green
- **Interior finish** Flocked
- **Exterior finish** Embossed texture
- **Size / EAN** 6 7 8 9 10 11
- **Packaging** 1 pair/bag - 10 pairs/bag - 100 pairs/carton
- **Complementary information** Guaranteed without silicone
available in 2 kind of packaging : individual bag and polybag of 10



PERFORMANCE RESULTS

Certification category 3

CE 0334



Dexterity EN 420 : 5/5

Type A



AJKOPT



3101X

Legends

EN 388 MECHANICAL HAZARDS



PERFORMANCE LEVELS

0-4 0-5 0-4 0-4 A-F (P)
 └─ Impact protection
 └─ Cut resistance according to ISO 13997
 └─ Puncture resistance
 └─ Tear resistance
 └─ Blade cut resistance
 └─ Abrasion resistance

EN 407 THERMAL RISKS heat and fire



PERFORMANCE LEVELS

0-4 0-4 0-4 0-4 0-4 0-4
 └─ Resistance to large quantities of molten metal
 └─ Resistance to small drops of molten metal
 └─ Radiant heat resistant
 └─ Convective heat resistance
 └─ Contact heat resistance
 └─ Burning behaviour

CHEMICAL RISKS

EN ISO 374-1 Type A



U V W X Y Z

A Methanol
B Acetone
C Acetonitrile
D Dichloromethane
E Carbon Disulfide
F Toluene
G Diethylamine
H Tetrahydrofuran
I Ethyl acetate

EN ISO 374-1 Type B



X Y Z

J n-Heptane
K Sodium hydroxide 40%
L Sulphuric acid 96%
M Nitric acid 65%
N Acetic acid 99%
O Ammonia 25%
P Hydrogen peroxide 30%
S Hydrofluoric acid 40%
T Formaldehyde 37%

EN ISO 374-1 Type C



MICRO-ORGANISMS

EN ISO 374-5



Protection against bacteria, fungi

EN ISO 374-5



Protection against bacteria, fungi, virus

VIRUS



COLD HAZARDS

PERFORMANCE LEVELS

0-4 0-4 0 or 1
 └─ Water permeability
 └─ Contact cold resistance
 └─ Convective cold resistance



RADIOACTIVE CONTAMINATION



CUT

CUT RESISTANCE

A1 ≥ 200 G	A4 ≥ 1500 G	A7 ≥ 4000 G
A2 ≥ 500 G	A5 ≥ 2200 G	A8 ≥ 5000 G
A3 ≥ 1000 G	A6 ≥ 3000 G	A9 ≥ 6000 G

For more details: www.mapa-pro.com

MAPA
PROFESSIONAL

www.mapa-pro.com

SPECIFIC ADVANTAGES

- Dexterity and comfort, due to the anatomical shape and the quality of the flock-lining
- Longer service life: excellent mechanical resistance (abrasion, perforation)
- Available in vending machine packaging

MAIN FIELDS OF USE

Automotive/mechanical industry

- Treating/degreasing metals with solvents
- Machining parts using cutting oil

Local Authorities (Cleaning)

- Handling aggressive chemical products

Construction Industry (Carpenters/Joiners)

- Handling PVC-based glues
- Preparing coatings, varnishes

Construction Industry (Masons / Plasterers)

- Handling oils, solvents, detergents

Local Authorities (Parks and Public Spaces)

- Plant Treatment Products

INSTRUCTIONS FOR USE

Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, because
- the conditions of use at workplace may differ from the "CE"-type tests.
- Persons sensitised to dithiocarbamates and thiazoles should not use these gloves.
- Put the gloves on dry, clean hands.
- Do not use the gloves in contact with a chemical for a duration in excess of the measured breakthrough time. Refer to the website www.mapa-pro.com or contact the Technical Customer Service - MAPA PROFESSIONNEL (stc.mapaspontex@mapaspontex.fr) in order to know this breakthrough time. Use 2 pairs alternatively when in long duration contact with a solvent.
- Turn the cuff end down in order to prevent a hazardous chemical from dripping onto the arm.
- Inspect the gloves for cracks or snags before reusing them.

Storage conditions

- Store the gloves in their original packaging protected from light, humidity and heat.

Laundering conditions

- Before taking off the gloves, clean them as appropriate :
- in use with paints, pigments and inks : wipe with a clean cloth dampened with a suitable solvent, and rub over with a dry cloth
- in use with a solvent (dilutents, etc...) : rub over with a dry cloth
- in use with acids or alkalies : thoroughly rinse the gloves under running water, and rub over with a dry cloth
- Caution : improper use of the gloves or submitting them to any cleaning or laundering process which is not specifically recommended can alter their performance levels.

Drying conditions

- Ensure the inside of the gloves is dry before putting them on again.

LEGISLATION

This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council. This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).

- **UE type certificate or CE type examination certificate** : 0075/014/162/08/18/1631
- **Issued by the notified body nr** : 0075 - C.T.C. – 4 rue Hermann Frenkel - F- 69367 LYON Cedex 07
- **Quality assurance certificat** : 0334 Asqual 14 rue des Reculettes -F-75013 PARIS