

Ultrane 510

DESCRIPTION AND GENERAL PROPERTIES

Material Water-based polymer
Length (inches) 8.66 - 10.63
Wrist Knitted wrist
Colour/Color Green
Interior finish Seamless textile support
Exterior finish Ventilated back
Size / EAN 6 7 8 9 10 11
Packaging 1 pair/bag - 12 pairs/bag - 96 pairs/carton
Complementary information Silicone and DMF Free
Oeko-tex®



PERFORMANCE RESULTS

Certification category 2



Dexterity EN 420 : 5/5

4131X

Legends

EN 388 MECHANICAL HAZARDS



PERFORMANCE LEVELS

0-4 0-5 0-4 0-4 A-F (P)
 Impact protection
 Cut resistance according to ISO 13997
 Puncture resistance
 Tear resistance
 Blade cut resistance
 Abrasion resistance

EN 407 THERMAL RISKS heat and fire



PERFORMANCE LEVELS

0-4 0-4 0-4 0-4 0-4 0-4
 Resistance to large quantities of molten metal
 Resistance to small drops of molten metal
 Radiant heat resistant
 Convective heat resistance
 Contact heat resistance
 Burning behaviour

CHEMICAL RISKS

EN ISO 374-1 Type A



U V W X Y Z

A Methanol
 B Acetone
 C Acetonitrile
 D Dichloromethane
 E Carbon Disulfide
 F Toluene
 G Diethylamine
 H Tetrahydrofuran
 I Ethyl acetate

EN ISO 374-1 Type B



X Y Z

J n-Heptane
 K Sodium hydroxide 40%
 L Sulphuric acid 96%
 M Nitric acid 65%
 N Acetic acid 99%
 O Ammonia 25%
 P Hydrogen peroxide 30%
 S Hydrofluoric acid 40%
 T Formaldehyde 37%

EN ISO 374-1 Type C



MICRO-ORGANISMS

EN ISO 374-5



Protection against bacteria, fungi

EN ISO 374-5



Protection against bacteria, fungi, virus

VIRUS



EN 511



COLD HAZARDS

PERFORMANCE LEVELS

0-4 0-4 0 or 1
 Water permeability
 Contact cold resistance
 Convective cold resistance



EN 421

RADIOACTIVE CONTAMINATION



CUT

CUT RESISTANCE

A1 ≥ 200 G A4 ≥ 1500 G A7 ≥ 4000 G
 A2 ≥ 500 G A5 ≥ 2200 G A8 ≥ 5000 G
 A3 ≥ 1000 G A6 ≥ 3000 G A9 ≥ 6000 G

For more details: www.mapa-pro.com

MAPA
PROFESSIONAL
www.mapa-pro.com

SPECIFIC ADVANTAGES

Breathable coating to have a better comfort in use
Anatomical shape: close fit for precision
Durable for a long-wear
OEKO-TEX®

MAIN FIELDS OF USE

Automotive/mechanical industry

Precision mechanical work
Precision assembly
Automotive assembly
Mechanical maintenance
Assembly of small parts
Fitting small screws and fasteners

Electronics

Assembly of electrical components
Microprocessor handling

Cosmetics and Pharmaceutical industry

Cosmetics preparation
Medicine manufacturing

INSTRUCTIONS FOR USE

Instructions for use

It is recommended to check that the gloves are suitable for the intended use, because the conditions of use in the workplace may differ from the tests performed in the laboratory.
It is recommended to not use them next to moving machinery
It is not recommended for persons sensitised to natural latex(wrist with elastic natural rubber).
Put the gloves on dry, clean hands.
Ensure the inside of the gloves is dry before putting them on again.

Storage conditions

Store the gloves in their original packaging protected from heat, light and humidity.

Laundering conditions

Caution : using the gloves or submitting them to a cleaning or laundering process that is not specifically recommended can alter their performance levels.

LEGISLATION

This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council. This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).

UE type certificate or CE type examination certificate : 0075/014/162/01/19/0133

Issued by the notified body nr : CTC - 4 rue Hermann Frenkel- 69367 Lyon cedex 07 - France - 0075