Templce 700

DESCRIPTION AND GENERAL PROPERTIES

Material Nitrile GRIP&PROOF coating

Length (inches) 9.50

Thickness (inches) Hvy. Wt.

Wrist Knitted wrist

Colour/Color Black / Blue

Interior finish Knitted thermal protection

Exterior finish Non-slip grip

Size / EAN 7 8 9 10

Packaging 1 pair/bag - 12 pairs/bag - 72 pairs/carton



PERFORMANCE RESULTS

Certification category 2









EN ISO 374-1

Type A

UVWXYZ

D

Ε

G

Methanol

Acetonitrile

Dichloromethane

Carbon Disulfide

Tetrahydrofurane

ANSI

Acetone


Toluene

Diethylamine

Ethyl acetate

Dexterity EN 420:5/5





L Burning behaviour

THERMAL RISKS heat and fire

PERFORMANCE LEVELS 0-4 0-4 0-4 0-4 0-4 Resistance to large quantities of molten metal Resistance to small drops of molten metal Radiant heat resistant Convective heat resistance Contact heat resistance

CHEMICAL RISKS

EN ISO 374-1 Type B

CUT RESISTANCE

A1 ≥ 200 G

A2 ≥ 500 G

A3 ≥ 1000 G



Sodium hydroxide 40% Sulphuric acid 96%

EN ISO 374-1

Type C

- M Nitric acid 65% N Acetic acid 99%
- 0 Ammonia 25%
- Hydrogen peroxide 30%
- Hydrofluoric acid 40%

A4 ≥ 1500 G

A5 ≥ 2200 G

A6 ≥ 3000 G

A7 $\geq 4000 \text{ G}$

A8 ≥ 5000 G

A9 > 6000 G

Formaldehyde 37%

MICRO-ORGANISMS

EN ISO 374-5



Potection against bacteria,

EN ISO 374-5



Potection against bacteria, fungi, virus

VIRUS



COLD HAZARDS PERFORMANCE LEVELS

0-4 0-4 0 or 1 Water permeability
■ Water permea Contact cold resistance Convective cold resistance

RADIOACTIVE CONTAMINATION

For more details: www.mapa-pro.com



SPECIFIC ADVANTAGES

Coating 5 times as durable than standard gloves on the market

Excellent grip when handling wet parts

Stay dry when working in wet conditions

Washable until 5 cleaning cycles (see laundering and drying conditions)

Suitable for frozen, dry and some fatty foods use according to the French law of November 9th, 1994 and to the European Directive CEE 1935/2004

MAIN FIELDS OF USE

Transport, logistics

Order preparation

Other industries

Maintenance in wet or cold environments Construction materials handling

Local Authorities (Waste Collection and Processing)

Waste collection

Local Authorities (Catering Services) Local Authorities (Parks and Public Spaces)

Public park maintenance

Local Authorities (Roads and Highways)

Maintaining the roads

INSTRUCTIONS FOR USE

Instructions for use

It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at workplace may differ from the «CE»-type tests.

It is not recommended for persons sensitised to natural rubber latex or dithiocarbamates to use these gloves.

Put the gloves on dry, clean hands.

Ensure the inside of the gloves is dry before putting them on again.

The gloves may lose their insulating property in the wet state.

Storage conditions

Store the glove in their original packaging protected from heat, light and humidity.

Laundering conditions

Performances of the 700 are not negatively affected by cleaning up to 5 cleaning cycles (5 successive washes done on unworn gloves) made with a household washing machine and a standard liquid detergent, synthetic program, temperature 60 ° C and spin drying at 400 rotations per minute.

Drying conditions

Trumble drying at 60°C maximum Put the gloves on dry, clean hands. Ensure the inside of the gloves is dry before putting them on again.

Food contact US

FDA 21CFR 177.2600

LEGISLATION

This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council. This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).

UE type certificate or CE type examination certificate: 0075/014/162/08/18/1671

Issued by the notified body nr: 0075 - CTC - 4 rue Hermann FENKEL - F 69367 LYON CEDEX 07

