

SOFTANE™ Tradition

JALARTIC SAS J0257

Softane™
Tradition

S3 CI SRC
EN ISO 20345:2011
36 to 48

- Full grain **AP 23** leather
- **Softane™** dual-density sole



- ❖ Natural-coloured, fur-lined boot with 2 leather side tabs for rapid pull-on.
- ❖ Isothermal lining for better protection against cold.
- ❖ Upper in water and oil resistant full grain **AP 23** leather, exclusive to Jallatte :
 - ❖ **10 to 15%** (2.4 mm) **thicker** than most leathers used for safety footwear.
 - ❖ **Resistance to penetration of water vapour three times higher** than the minimum fixed by European Standard.
- ❖ Flat binding at top of quarters.
- ❖ Counter to maintain a snug-fitting heel.
- ❖ Inlay covering the entire surface of the foot, removable, antistatic, treated against bacteria, containing active carbon, anatomical and with heel cushioning. High capacity for absorbing and evaporating perspiration.
- ❖ Perforated steel toe-cap (patented) – 200 J.
- ❖ Puncture-resistant stainless steel midsole .
- ❖ Dual density **Softane™** sole with progressive shock absorber to protect back and joints from vibrations. Self cleaning sole pattern. Multi-directional treads. Rounded heel pressure zone for comfort and stability.

Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

Requirement SRC (SRA+SRB)

SRA Test ground : ceramic/lubricant : water and detergent

On flat 0,58 (>0,32) – On the heel 0,54 (>0,28)

SRB Test ground steel/lubricant : glycerine

On flat 0,37 (>0,18) – On the heel: 0,14 (>0,13)

- ✓ Wraps round the foot for increased stability when walking.
- ✓ Outsole density = 1.02 / Comfort layer density = 0.45
- ✓ Highly resistant to oils and hydrocarbons.
- ✓ Abrasion resistance : 80 mm³
- ✓ Heel shock absorption 29 Joules.

Weight	Gross weight (42): 1760 g / Net weight (42): 1440 g												
Size	36	37	38	39	40	41	42	43	44	45	46	47	48
Packaging	5 pairs												
Dimensions	625 x 425 x 345												



 **Jallatte®**

www.jallatte.com