

LUCANIA 4112



CHARACTERISTICS

- Permanently attached to the kernmantle rope lifeline. Supplied with a shock absorber and a 12 mm diameter polyester kernmantle rope lifeline
- Steel karabiner (opening 18 mm) for attaching to a harness
- Wear-resistant eye to protect loops from damage
- The attachment of the lifeline is secured with a strong transparent cover sheath that protects the end, making the stitches visible for easy inspection
- Equipped with an NFC chip under the label designed for mapping users and keeping track of inspection schedules
- Length: 20 mm
- Maximum resistance: 15 kN

Article number: 8.84.112.00

SUITABLE FOR WORK IN, E.G.:

- Scaffolding
- Construction
- Installation technology
- Aerial platforms
- Offshore
- Petrochemicals

PACKAGING

- 1 piece per polybag
- 8 pieces per case

CE 0598
EN 353-2:2002

ITEM INFORMATION

SIZE	ARTICLE NO.	EAN CODE 1 PIECE (POLYBAG)	EAN CODE 8 PIECES (CASE)
One size	8.84.112.00	8718249049071	8718249049088

STORAGE REQUIREMENTS

During transport, keep the product in its packaging, well away from any cutting surface; clean it with water, wipe it with a rag and hang it up in a well-ventilated location, to let it dry naturally and away from a naked flame or heat source; follow the same procedure for components that have become damp during use. The system must be stored in its packaging in a dry, well aired place protected from extremes of temperature.

TESTING INSTITUTE

This fall protection is certified by: SATRA Technology Europe Ltd (Notified Body no. 2777), Bracetown Business Park, Clonee, Dublin D15 YN2P, Ireland.

DECLARATION OF CONFORMITY

For a copy of the declaration of conformity, please refer to the following web link:
www.oxxa-safety.com/doc

RELATED PRODUCTS



FUJI 4015
 Harness 3D
 Article no. 8.84.015.00



MACAULAY 4150
 Steel karabiner
 Article no. 8.84.150.00



HUNTINGTON 4111
 Rope Grab fall arrest device with
 shock absorber and lifeline
 Article no. 8.84.111.00

YOUR SUPPLIER: